

# SANITARY VALVES

## HIGH PURITY BUTTERFLY VALVE

### FEATURES

- INTERNAL SURFACE FINISH IS 0.8 RA.
- EXTERNAL SURFACE FINISH IS 0.8 RA ~ 1.6 RA.
- TUBE O.D. FULL PORT
- AVAILABLE MATERIALS SS 304, SS 316 & SS 316L.
- WORKING PRESSURE -0.9 TO 10 BARS
- AVAILABLE MATERIAL SEATS: SILICON, EPDM & VITON
- AVAILABLE ENDS: CLAMP, WELD, MALE THREADED, FEMALE TREADED, (RTJ, IDF, IDN SMS, 3A.....)
- STAINLESS STEEL ACTUATOR AVAILABLE ON REQUEST
- MANUFACTURED IN ISO 9001 APPROVED FACILITY
- APPLICATIONS: BEER, DAIRY, BEVERAGE, PHARMACY

**Series 9RS**




### SANITARY WELDED BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"

Standard: DIN, SMS, ISO

Material quality: SUS304, SUS316L



### DIMENSION (mm)

Size ( ISO )	A	B	D	L	H	Kg
20	50	78	19.05	130	82	1.2
25	50	78	25.4	130	82	1.2
32	50	78	31.8	130	82	1.05
38	50	86	38.1	130	86	1.2
51	52	102	50.8	140	96	1.7
63	56	115	63.5	150	103	2.1
76	56	128	76.1	150	110	2.4
89	60	139	88.9	170	116	2.7
102	64	154	101.6	170	122	3.05
108	64	159	108	170	126	3.15
133	80	138	133	190	138	5.2
159	90	215	159	190	153	9.2

# SANITARY VALVES


## HIGH PURITY BUTTERFLY VALVE

### SANITARY QUICK-INSTALL BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"


Standard: DIN, SMS, ISO

Material quality : SUS304, SUS316L



### DIMENSION (mm)

Size ( ISO )	A	B	D	L	H	Kg
20	66	78	50.5	130	82	1.35
25	66	78	50.5	130	82	1.35
32	66	78	50.5	130	82	1.2
38	70	86	50.5	130	86	1.3
51	76	102	64	140	96	1.85
63	98	115	77.5	150	103	2.25
76	98	128	91	150	110	2.6
89	102	139	106	170	116	3
102	106	154	119	170	122	3.6
108	106	159	119	170	126	3.6
133	140	185	145	190	138	6.5
159	260	215	172	190	153	11



# SANITARY VALVES


## HIGH PURITY BUTTERFLY VALVE

### SANITARY SMS THREADED BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"


Standard: DIN, SMS, ISO

Material quality : SUS304, SUS316L



### DIMENSION (mm)

Size ( SMS )	A	B	D	L	H	Kg
25	66	78	40×1/6	130	82	1.3
32	66	78	48×1/6	130	82	1.3
38	70	86	60×1/6	130	86	1.7
51	76	102	70×1/6	140	96	2.2
63	80	115	85×1/6	150	103	2.9
76	84	128	98×1/6	150	110	3.4
89	90	139	110×1/6	170	116	3.9
102	104	159	132×1/6	170	126	5.5



# SANITARY VALVES


## HIGH PURITY BUTTERFLY VALVE

### SANITARY QUICK-INSTALL BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"


Standard: DIN、SMS、ISO

Material quality : SUS304、SUS316L



### DIMENSION (mm)

Size ( ISO )	A	B	D	L	H	Kg
20	66	78	50.5	130	82	1.35
25	66	78	50.5	130	82	1.35
32	66	78	50.5	130	82	1.2
38	70	86	50.5	130	86	1.3
51	76	102	64	140	96	1.85
63	98	115	77.5	150	103	2.25
76	98	128	91	150	110	2.6
89	102	139	106	170	116	3
102	106	154	119	170	122	3.6
108	106	159	119	170	126	3.6
133	140	185	145	190	138	6.5
159	260	215	172	190	153	11





# SANITARY VALVES


## HIGH PURITY BUTTERFLY VALVE

Sanitary three piece butterfly valve

Specification: DN20-150 , 1"-6"


Standard: DIN, SMS, ISO

Material quality : SUS304, SUS316L



### DIMENSION (mm)

Size ( ISO )	A	B	D	L	H	Kg
20	100	78	19.05	130	82	2.1
25	100	78	25.4	130	82	2.1
32	100	78	31.8	130	82	2.05
38	100	86	38.1	130	86	2.3
51	104	102	50.8	140	96	3.25
63	112	115	63.5	150	103	4.15
76	112	128	76.1	150	110	4.3
89	120	139	88.9	170	115	5.4
102	128	154	101.6	170	122	6.3
108	128	159	108	170	126	6.7
133	160	185	133	190	138	10.4
159	180	215	159	190	153	18.4



# SANITARY VALVES


## HIGH PURITY BUTTERFLY VALVE

### SANITARY BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"


Standard: DIN, SMS, ISO

Material quality : SUS304, SUS316L



### DIMENSION (mm)

Size ( DIN )	A	B	D	L	H	Kg
20	66	78	44×1/6	130	82	1.35
25	66	78	52×1/6	130	82	1.35
32	70	86	58×1/6	130	86	1.45
40	74	90	65×1/6	130	90	1.75
50	76	106	78×1/6	140	98	2.45
65	84	124	95×1/6	150	108	3.2
80	90	139	110×1/4	170	116	3.85
100	108	159	130×1/4	170	126	5.45
125	130	190	160×1/4	190	141	7.2
150	150	220	190×1/4	190	156	12.2




# SANITARY VALVES

## HIGH PURITY BUTTERFLY VALVE

### SANITARY CAMPLED BUTTERFLY VALVE

Specification: DN20-150 , 1"-4"

Material quality : SUS304、SUS316L



### DIMENSION (mm)

Size ( DN )	A	D	L	H
40	38	85	130	122
50	39	95	130	127
65	42	107	140	133
80	43	125	150	142
100	46	156	160	158



# SANITARY VALVES

## HIGH PURITY BUTTERFLY VALVE

### SANITARY FLANGED BUTTERFLY VALVE

Specification: DN20-150 , 1"-6"

Material quality : SUS304、SUS316L



Specification: DN20-150 , 1"-6"

Standard: DIN、SMS、ISO

Material quality : SUS304、SUS316L







tfv usaoperation

contact@tfvusao.com  
www.tfvusao.com

Call free from USA and CANADA

t: 1-866-TFV-USA0 (838-8726)

# SANITARY VALVES

## HIGH PURITY BUTTERFLY VALVE

SANITARY PNEUMATIC AND ELECTRIC OPERATION OPTIONS





# SANITARY VALVES

## HIGH PURITY BUTTERFLY VALVE

### HOW TO ORDER

VALVE BODY DESIGN (SERIES)	FEATURES		MATERIAL			ENDS	CLASS	SIZE		OPERATION	
			BODY	DISC	SEAT						
9RS Resilient Seated SANITARY Butterfly Valve	NONE	NONE	3 CF8M	3 316SS	L SILICON	B Welded	0 ANSI 150#	01	1"	L	Manual Position Op Lever
	D	DIN	4 CF8	4 304 SS	E EPDM	C Clamp		01.5	1 1/2"		
	M	SMS	5 CF3M	5 316L SS	F FPM	T Threaded		02	2"		
	I	ISO	7 CF3	7 304L SS		W Wafer		02.5	2 1/2"	F	On-Off
	D	IDF				F Flanged		03	3"		
	R	RJT				H Three Pcs		03	3"	P	Pneumatic Actuator
	S	DS				M Two Different Ends		04	4"		
	A	3A						05	5"	B	Bare Shaft
	B	BS						06	6"		

### Example

Sanitary Butterfly Valve According with 3A, Body & Disc 316L, Seat EPDM, CLAMP ANSI 150# Size 6" with Lever.

**9RSA-55E-C006L**

